

DRGONF1Y

ACTIVE DIRECTORY ATTACK PATHS

A PRACTICAL FIELD MANUAL FOR ASSESSMENT,
EXPLOITATION, DETECTION & DEFENSE



2026 FIFTH EDITION - REVISION 5.1
PRACTITIONER EDITION

DRGONF1Y

CYBERSECURITY CONSULTING LLC

BLOODHOUND • KERBEROS • AD CS • LAPS • DELEGATION • HYBRID IDENTITY

THE ORIGINAL VISUAL IDENTITY WITH A CLEARER ROUTE INTO THE BOOK

F-02 Title and Learning Contract

DRG0NF1Y ACTIVE DIRECTORY ATTACK PATHS

2026 Fifth Edition Revision 5.1 - Practitioner Edition

This field manual teaches security reasoning through evidence, prerequisites, manual verification, minimal authorized proof, cleanup, detection, remediation, and retest. Commands are representative and version-sensitive; installed help and primary documentation remain authoritative.

Discover -> Enumerate -> Validate -> Control -> Prove -> Clean up -> Report

Reader promise	How Revision 5.1 supports it
Find the next page	A visible table of contents maps physical pages, chapters, decision libraries, references, and appendices.
Know how to read	Page 9 explains learning, field, lab, defensive, and reporting modes.
Know what to do next	Page 10 routes common lab results to the correct methodology or attack-path family.
Keep the original identity	The illustrated shield-and-dragon cover is restored; only the edition badge is updated.

Version decision. This is Revision 5.1 because it corrects navigation and reader workflow without adding a new major attack-path family.

AUTHORIZATION IS A PREREQUISITE

F-03 Copyright Scope and Responsible Use

Copyright (c) 2026 DRG0NF1Y Cybersecurity Consulting LLC. All rights reserved. Fifth Edition Revision 5.1 publication build.

This book is for defensive security professionals, penetration testers, red-team students, administrators, instructors, and learners working in intentionally vulnerable laboratories or explicitly authorized assessments. Use commands and procedures only against systems for which the operator has authorization.

Boundary	Required practice
Scope	Record domains, forests, subnets, identities, techniques, and exclusions before testing.
Minimal proof	Prove the security-boundary change with the least disruptive reversible action.
Secrets	Keep passwords, hashes, tickets, keys, certificates, and dumps out of publication screenshots.
Cleanup	Track every changed object, file, listener, route, credential artifact, and rollback verification.
Claims	Separate demonstrated capability, supported inference, and untested hypothesis.

Responsible-use rule. If authorization, rollback ownership, or the stop condition is unclear, pause before changing state.

START WITH THE ROUTE THAT MATCHES YOUR CURRENT EVIDENCE

F-04 Table of Contents - Book Map

Section	Purpose	Physical pages
Part I - Foundations	AD model, rights, Kerberos/NTLM, Tier 0	11-17
Part II - Assessment methodology	Scope, recon, black box, PJPT, atlas, CRTP, DNS, authenticated enum, BloodHound	18-154
Part III - Credential/Kerberos	Passwords, roasting, stores, hash/ticket paths	155-181
Part IV - Authorization/control	ACLs, groups, GPO, local admin, sessions	182-214
Part V - Enterprise AD	LAPS/gMSA, delegation, AD CS, DCSync, trusts, hybrid	215-273
Part VI - Detection/reporting	Detection, evidence, remediation, practice, troubleshooting	274-289
Part VII - Visual guide/labs	Diagrams, GOAD notes, six guided labs	290-315
Part VIII - Advanced/reference	AD CS, hybrid, cases, exercises, simulation, endnotes, index	316-344
Appendices	Linux, BloodHound, Windows, IF-THEN, MITRE, worksheets, glossary, bibliography	345-357
University HB Chain revision	Reusable chain patterns, validation, defense, cleanup	358-400

Navigation. The PDF bookmark panel mirrors the specialized routes. The next four contents pages provide physical page numbers for chapters and decision libraries.

FOUNDATIONS, ASSESSMENT METHODOLOGY, AND CREDENTIAL PATHS

F-05 Table of Contents - Chapters 1-14

Chapter	Title	Page
1	AD Security Model	11
2	Rights, Privileges, Permissions	13
3	Kerberos and NTLM	14
4	Tier 0 and Privileged Access	16
5	Scope and Rules of Engagement	18
6	Reconnaissance	19
7	DNS and Domain Orientation	140
8	Authenticated Enumeration	141
9	BloodHound Attack-Path Analysis	142
10	Password and Secret Hygiene	155
11	Kerberoasting	158
12	AS-REP Roasting	165
13	Credential Stores and Session Exposure	167
14	Pass-the-Hash and Ticket Paths	179

Start rule. With zero credentials, use Chapter 5 for scope, Chapter 6 for recon, then enter the Black Box Methodology at page 21.

*AUTHORIZATION, ENTERPRISE CONTROL PLANES, DEFENSE, AND PRACTICE***F-06 Table of Contents - Chapters 15-30**

Chapter	Title	Page
15	GenericAll and GenericWrite	182
16	WriteDACL and WriteOwner	189
17	Group Membership and Password Control	196
18	GPO and OU Control	203
19	Local Administrator and Session Paths	210
20	Windows LAPS and gMSA	215
21	Kerberos Delegation	217
22	AD CS and Certificate Services	224
23	DCSync and Replication Rights	232
24	Trusts and Multi-Domain Paths	239
25	Hybrid AD and Microsoft Entra	241
26	Detection Engineering	274
27	Evidence and Attack-Path Reporting	276
28	Remediation and Retest	278
29	C RTP and GOAD Practice Program	279
30	Troubleshooting and Decision Trees	281

Edge rule. Use Chapters 15-25 only after a live ACL, service, delegation, certificate, replication, trust, or hybrid prerequisite is verified.

VISUAL LEARNING, GUIDED LABS, ADVANCED TOPICS, REFERENCES, AND TEACHING MATERIAL

F-07 Table of Contents - Chapters 31-50 and Appendices

Chapter	Title	Page
31	Attack-Path Diagrams	290
32	GOAD Field Notes and Screenshots	294
33	Guided Lab 1 - Reconnaissance	303
34	Guided Lab 2 - Authenticated Enumeration	305
35	Guided Lab 3 - Kerberos	307
36	Guided Lab 4 - ACL Attack Paths	309
37	Guided Lab 5 - AD CS	311
38	Guided Lab 6 - DCSync	313
39	AD CS Deep Dive	316
40	Hybrid Identity Deep Dive	318
41	Case Studies	321
42	Exercises and Answer Key	332
43	CRTP-Style Final Simulation	335
44	Instructor Edition Orientation	Instructor only
45	GOAD Screenshot Walkthroughs	Instructor only
46	Detection Event Encyclopedia	Instructor only
47	Printable Operator Field Cards	Instructor only
48	Instructor-Led Capstone	Instructor only
49	Formal Endnotes	337
50	Topic Index	341
A-G	Appendices and quick references	345

Edition note. Chapters 44-48 appear only in the Instructor Edition. Student and Practitioner editions route directly from Chapter 43 to Chapters 49-50.

THE SHORTEST ROUTE FROM AN OBSERVATION TO THE CORRECT FIELD CARD

F-08 Table of Contents - Decision Libraries

Cards	Coverage	Pages
B-01 to B-10	Scope, interface, discovery, services, AD roles, DNS	21-30
B-11 to B-20	Time, SMB/LDAP/RPC/web, users, AS-REP, first credential	31-40
B-21 to B-30	Authenticated inventory, shares, roasting, AD CS, BloodHound, shell, privilege	41-50
B-31 to B-41	SQL, relay, GPO, delegation, pivots, domain proof, recovery, reporting	51-61
P-01 to P-08	PJPT route, pass-the-password, Golden and Silver tickets	62-69
P-09 to P-16	GPP cpassword, LLMNR/NBT-NS, Responder, mitm6	70-77
P-17 to P-24	Token impersonation, file transfer, integrated PJPT chain, sources	78-85
A-01 to A-06	Credential-free enum, roasting, PtP/PtH/PtT/PtC	86-91
A-07 to A-13	ACL model and full WriteOwner-to-PKINIT chain	92-98
A-14 to A-20	GPO/GPP, relay, RBCD, delegation, managed secrets, DCSync, tickets	99-105
A-21 to A-27	Trusts, built-in operators, token privileges, service ACLs, secret sources	106-112
A-28 to A-36	Tasks/services, SQL, movement, AD CS, troubleshooting, pivot, closure	113-121
6A to 6R	CRTP result-driven field upgrade	122-139
HB revision	Portable multi-stage chains and defensive validation	358-400

If the test succeeds: you have a named observation. Jump to its card, verify prerequisites, and perform minimal proof.

If the test fails: you do not yet have evidence. Return to B-01 and advance sequentially until a gate produces it.

CHOOSE A READING MODE, THEN FOLLOW RESULTS RATHER THAN CHAPTER ORDER

F-09 How to Use This Book

Mode	What to do	Best starting point
Learn	Explain the protocol, security boundary, prerequisite, and failure states in your own words.	Chapters 1-4, then the relevant chapter
Black-box lab	Begin with no assumed credentials and follow B-01 through the first validated branch.	Page 21
Technique lab	Choose one P or A card; satisfy every prerequisite; use an inert proof and exact cleanup.	Pages 62 or 86
Exam practice	Use the evidence ledger and decision cards; hide answer material and enforce a stop timer.	Pages 9-10, then page 21
Defend	For each transition, identify telemetry, a path-breaking remediation, and a retest query.	Chapter 26 and each card's defense row
Report	Convert the chain into evidence, impact, limits, cleanup, remediation, and retest statements.	Chapter 27 and A-36

Working loop: Question -> Evidence -> Prerequisite -> Minimal proof -> Cleanup -> Next branch

Page element	Meaning
Trigger	The observation that justifies opening this path.
Prerequisites	Conditions that must already be true; unmet conditions are stop gates.
Manual verification	Native or independent corroboration before mutation.
If it succeeds / fails	The next page family or diagnostic question; do not repeat a successful invasive action.
Evidence and cleanup	What to retain, protect, reverse, and independently verify.

Do not read linearly during a lab. Use the contents to learn; use the decision libraries to operate. Re-enumerate after every new identity, credential, token, host-control level, route, or domain boundary.

ONE RESULT SHOULD PRODUCE ONE DEFENSIBLE NEXT QUESTION

F-10 How to Run a Lab - IF Result THEN Route

Observed result	Next route
No confirmed domain or DC	B-04 to B-10: interface, discovery, services, AD role, DNS
Domain known; no credential	B-11 to B-18: time, anonymous services, sourced users, AS-REP
Valid username or credential	B-19 to B-25: ledger, protocol matrix, LDAP/shares/roasting/AD CS/BloodHound
Password, hash, ticket, or certificate	P-02/P-03 and A-05/A-06: validate artifact against compatible protocols
BloodHound ACL edge	B-27 and A-07: verify live owner, DACL, group token, property, and target
WinRM/RDP/SMB execution succeeds	B-29 and A-30: obtain the least disruptive shell; run foothold baseline
MSSQL authentication succeeds	B-31 and A-29: separate login, impersonation, sysadmin, OS token, and links
Relay prerequisites are present	B-32, P-11 to P-16, A-15: analyze first; select one source/target/action
GPP or GPO control is found	P-09/P-10, B-33, A-14: separate cpassword, GPC, GPT, gPLink, and scope
AD CS condition is found	B-24/B-34 and A-31 to A-33: verify end-to-end issuance and mapping
New identity, host admin, or subnet	B-35 and A-35: repeat only affected discovery and authenticated gates
DCSync or Tier-0 proof succeeds	A-19 and A-36: stop active exploitation, clean up, preserve evidence, report

Lab rhythm

1. Record scope, source host, time, tool version, identity, target, and question.
2. Run the least invasive discovery or verification step.
3. Classify success, failure, and what the result does not prove.
4. Perform one minimal authorized proof; stop when the objective is met.
5. Clean up, verify restoration, re-enumerate changed boundaries, and write the finding.

If the test succeeds: the result changes capability. Update the ledger and follow exactly one named route.

If the test fails: the result does not change capability. Diagnose reachability, DNS/time, authentication, authorization, protection, or tool syntax.

Part I - Active Directory Foundations 1. AD Security Model

Active Directory Domain Services is an identity and authorization system. Users, computers, groups, services, policies, certificates, and administrative relationships become security principals or securable objects connected by permissions. Attack paths emerge when a principal that begins with limited trust can traverse those relationships toward a higher-value identity or control plane.

- Authentication answers: who are you?
- Authorization answers: what may you do?
- A security principal may be a user, computer, group, or service identity.
- An object ACL can create a privilege path even when no software vulnerability exists.
- A domain compromise is usually a chain of relationships, not one exploit.

Attack-path thinking

LOW-PRIV USER

```
|
├─ group membership
├─ writable object
├─ reusable credential
├─ privileged session
├─ GPO / delegation / certificate path
```

▼

INTERMEDIATE CONTROL

▼

TIER 0 / DIRECTORY CONTROL

Assessment questions

- What identities exist?

- What can each identity control?
- Where can each identity authenticate?
- Where is its administrator?
- What secrets or sessions become exposed when a host is controlled?
- Which paths reach Tier 0?

Facilitator checkpoint

- Have the learner identify the current identity and distinguish authentication from authorization.
- Require one manually verified edge before accepting a graph-derived path.
- Ask which evidence is demonstrated, inferred, or still missing.
- Record the least-invasive next validation step and the stop condition.

2. Rights, Privileges, Permissions and ACLs


Windows terminology matters. Rights or privileges are system-wide capabilities assigned to principals. Permissions are object-specific access controls represented by ACLs and ACEs. Effective access depends on group membership, inheritance, explicit allow/deny entries, ownership,

and sometimes powerful user rights.		
Concept	Example	Security question
User right / privilege	SeBackupPrivilege	Does the token provide a system-wide capability?
Permission	Write property on AD user	Which object and attribute can be changed?
ACL	DACL on group/GPO/OU	Who is allowed or denied?
ACE	Principal + right + inheritance	Is the entry direct or inherited?
Owner	Object owner	Can ownership be converted into permission control?

Native inspection

```
whoami /priv
whoami /groups
dsacls "<DISTINGUISHED_NAME>"
Get-Acl "AD:<DISTINGUISHED_NAME>" | Format-List
```

Microsoft emphasizes that highly privileged groups and accounts can affect the entire forest. The practical lesson is to identify both obvious privileged groups and less-obvious delegated permissions that lead to them.



3. Kerberos and NTLM

Figure 3.1. Kerberos authentication and ticket flow.

Kerberos is the preferred domain authentication protocol. NTLM remains relevant for compatibility and can become a lateral-movement risk when privileged credentials are reused or exposed. A tester should understand the protocol state before selecting tools.


Artifact	Purpose
TGT	Proves a principal has authenticated to the KDC and can request service tickets.
TGS	Service ticket for a particular SPN/service.
SPN	Maps a service instance to an account.
NTLM material	Password-derived authentication material used by NTLM-based flows.
PAC	Authorization information carried in Kerberos tickets.

Kerberos troubleshooting order

1. DNS
2. FQDN / realm spelling
3. Clock synchronization
4. KDC reachability
5. Account status
6. Ticket cache / credential validity
7. Only then change technique/tool

Kerberos troubleshooting worksheet

- Realm/FQDN and DNS resolution verified.
- Client and KDC time synchronization verified.
- KDC reachability and account status verified.
- Ticket cache state recorded before changing tools.



4. Tier 0 and Privileged Access

Figure 4.1. Tier 0, Tier 1, and Tier 2 privileged-access model.

For AD DS, Microsoft's current tier model separates Tier 0, Tier 1, and Tier 2 administrative identities, workstations, and managed assets. Tier 0 is the identity control plane: compromise of a Tier 0 asset or identity can enable control of the directory. The central rule is to never administer a more trusted tier from a less-trusted host.

Tier	Typical examples
Tier 0	Domain controllers; Enterprise Admins/Domain Admins/Administrators; AD CS when it can issue or manage authentication for privileged identities; Microsoft Entra Connect Sync infrastructure and other assets that can control AD.
Tier 1	Enterprise application/member servers and the identities/workstations that administer them.
Tier 2	End-user workstations and the identities/workstations that administer them.